

Models

		S160/30	S160/30AV	S160/30AVL	S200/30AV	S200/30AVL
Capacity kg/h with UR%	10÷15%	50	32÷50	32÷50	52÷79	52÷79
	20÷25%	---	26÷37	26÷37	38÷55	38÷55
	35÷40%	---	---	---	---	---
	40÷45%	---	---	20÷25	---	25÷32

Cylinder rotation

Speed	m/min	3.9	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4
Noise	dB	50	50	50	50	50

Net and packing dimension

Net dimension	Width (mm)	2200	2200	2200	2600	2600
	Depth (mm)	500	500	500	500	500
	Height (mm)	1100	1100	1100	1100	1100
Packing dimension	Width (mm)	2280	2280	2280	2690	2690
	Depth (mm)	610	610	610	610	610
	Height (mm)	1300	1300	1300	1300	1300
	Volume (m ³)	1.808	1.808	1.808	2.14	2.14
Net / Gross weight	kg	257 / 295	262 / 300	262 / 300	294 / 350	294 / 350

Motore ed aspirazione

Cylinder motor	kW	0.18	0.36	0.36	0.36	0.36
Speed adjust	Inverter	---	Standard	Standard	Standard	Standard
Basin motor	kW	0.18	0.18	0.18	0.18	0.18
Vacuum motor	kW	---	0.12	0.12	0.12	0.12

Electric heating data

Power supply	V / ph / Hz	230-240V 3~50/60Hz				
		230-240V 1~50/60Hz				
		380-415V 3N 50/60Hz				
		440-480V 3~ 60Hz				
Heating power	kW	13.2	13.2	13.2	16.8	16.8
Electric consumption	kW/h	8	8	8	10	10
Fuses (380-415V)	A	20	21	21	25.5	25.5

Electric heating electric data

Power supply	V / ph / Hz	230-240V 3~50/60Hz				
		230-240V 1~50/60Hz				
		380-415V 3N 50/60Hz				
		440-480V 3~ 60Hz				
Electric power	kW	0.36	0.48	0.48	0.48	0.48
Steam consumption	kg/h	35	35	35	40	40
Steam pressure	Bar	10 ÷ 12	10 ÷ 12	10 ÷ 12	10 ÷ 12	10 ÷ 12
Steam connection	inch	3/4 IN/OUT	3/4 IN/OUT	3/4 IN/OUT	3/4 IN/OUT	3/4 IN/OUT
Fuses (380-415V)	A	0.6	0.8	0.8	0.8	0.8