

Models GD

		GD6	GD6C
Ratio capacity	1:20	6	6
Drum dimensions	Diameter (mm)	571	571
	Depth (mm)	476	476
	Volume (dm ³)	112	112
Door diameter	mm	307	307
Drum speed	rpm	50 ÷ 55	50 ÷ 55

Net and packing dimensions

Net dimensions	Width (mm)	595	595
	Depth (mm)	585	585
	Height (mm)	850	850
Packing dimensions	Width (mm)	710	710
	Depth (mm)	630	630
	Height (mm)	980	980
	Volume (m ³)	0.44	0.44
Net / Gross weight	kg	39 ÷ 45	47 ÷ 53

Electric models data

Power supply	V / ph / Hz	230-240V 1~50/60Hz	230-240V 1~50/60Hz
		230-240V 3~50/60Hz	230-240V 3~50/60Hz
		380-415V~3N 50/60Hz	380-415V~3N 50/60Hz
		440-480V~3 50/60Hz	440-480V~3 50/60Hz
Electric thermal power	kW	1.95 ÷ 2.5 ÷ 3	1.95 ÷ 2.5 ÷ 3
Motor power	kW	0.2	0.2
Total electric power	kW	2.15 ÷ 2.7 ÷ 3.2	2.15 ÷ 2.7 ÷ 3.2
Fuse	A	10 ÷ 16 ÷ 16	10 ÷ 16 ÷ 16
Exhaust	Diameter (mm)	100	100
Noise	dB	<52	<52

The required environmental conditions to have the right performances are listed below:

- Laundry load with max 50% moisture
- Inlet air temperature 23°C
- 55% moisture on the inlet air
- Drying cycle: Regular drying temperature
- Heating power on models GD6-GD6C: 2500W