

Models GC

		1532	1732	1932	2132
Usable length	mm	1500	1650	1900	2100
Cylinder dimensions	Diameter (mm)	320	320	320	320
	Heated surface (m ²)				
Exhaust	Speed (mt/min)	1 ÷ 5	1 ÷ 5	1 ÷ 5	1 ÷ 5
	Number	1	1	2	2
	Diameter (mm)	100	100	2 x 100	2 x 100
Capacity	Extraction power (m ³ /h)	240	240	2 x 240	2 x 240
	kg/h	15 ÷ 28	18 ÷ 46	25 ÷ 50	27 ÷ 55
	Water evaporation (l/h)				
Noise	dB				

Net dimensions and packing

Net dimensions	Width (mm)	1890	2040	2410	2610
	Depth (mm)	720	720	720	720
	Height (mm)	1060	1060	1080	1080
Packing dimensions	Width (mm)				
	Depth (mm)				
	Height (mm)				
	Volume (m ³)				
Net / gross weight	kg				

Electric heated models

Power supply	V / ph / Hz	230-240V 3~50/60Hz			
		380-415V 3~N 50/60Hz			
		440-480V 3~ 60Hz			
Electric thermal power	kW	10 (13.5)	15.9	16	18
Motor power	kW	0.18	0.18	0.18	0.18
Total power	kW	10.18 (13.68)	16.08	16.18	18.18
Fuse	A	16 (20)÷32 (40)	25 ÷ 50	25 ÷ 50	32 ÷ 50

Gas heated models

Power supply	V / ph / Hz	230-240V 3~50/60Hz			
		380-415V 3~N 50/60Hz			
		440-480V 3~ 60Hz			
Gas thermal power	kW	12.6	14	16.3	18.06
Natural gas consumption	m ³ /h	1.21	1.33	2.26	2.58
Liquid gas consumption	kg/h	1.5	1.6	2	2.2
Motor power	kW	0.18	0.18	0.18	0.18
Total electric power	kW	0.5	0.5	0.5	0.5
Fuse	A	2 ÷ 2	2 ÷ 2	2 ÷ 2	2 ÷ 2

Introduction belts

Large introduction belts to help the operator even in case of large items to be ironed.



Ironing belts

The ironing belts made of NOMEX® felt and the antistatic strips. An easy and reliable solution.

