

Models GC

		2050	2650	3350
Working width	mm	2000	2600	3300
Cylinder dimensions	Diameter (mm)	500	500	500
	Heated surface (m ²)	3 - 310° covered roll	4 - 310° covered roll	5 - 310° covered roll
	Height floor feeding belts (mm)	1120	1120	1120
	Cylinder speed (mt/min)	1 ÷ 8	1 ÷ 8	1 ÷ 8
	Length folder	Optional	Optional	Optional
	Rear exit (pass through)	Optional	Optional	Optional
Exhaust	Number	1	2	2
	Diameter (mm)	1 x 153	2 x 153	2 x 153
	Flow (m ³ /h)	600	2 x 600	2 x 600
Capacity	kg/h	50 ÷ 70	60 ÷ 80	80 ÷ 120
	Evaporation (l/h)	35 ÷ 49	42 ÷ 56	56 ÷ 84

Net and packaging dimensions (*With folder and/or pass through)

Net dimensions	Width (mm)	2845	3445	4145
	Depth (mm)	1070 (*1417)	1070(*1417)	1070(*1417)
	Height (mm)	1420	1420	1420
Packaging dimension	Width (mm)	3415	3745	4445
	Depth (mm)	1153	1153	1153
	Height (mm)	1672	1672	1672
	Volume (m ³)	6.06	7.22	8.57
Net / Gross weight	kg	930(*1140)/972(*1182)	1180(*1435)/1470(*1518)	1430(*1480)/1740(*1790)
Noise	dB	< 65	< 65	< 65

Models with electric heating (*With length folder / **With length folder and pass through)

Power supply	V / ph / Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz
		380-415V 3~N 50/60Hz	380-415V 3~N 50/60Hz	380-415V 3~N 50/60Hz
		440-480V 3~ 60Hz	440-480V 3~ 60Hz	440-480V 3~ 60Hz
Thermal electric power	kW	31.5	40.5	54
Motor power	kW	0.62 (*+0.56/**+0.74)	0.87(*+0.56/**+0.74)	0.87(*+0.56/**+0.74)
Total power	kW	32.12 (*32.68/**32.86)	41.37(*41.93/**42.11)	54.87(*55.43/**55.61)
Fuses	A	50 ÷ 100	63 ÷ 125	100 ÷ 160

Models with gas heating (*With length folder / **With length folder and pass through)

Power supply	V / ph / Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz
		380-415V 3~N 50Hz	380-415V 3~N 50Hz	380-415V 3~N 50Hz
		440-480V 3~ 60Hz	440-480V 3~ 60Hz	440-480V 3~ 60Hz
Gas thermal power	kW	40	55	69
Natural gas consumption	m ³ /h	4.2	5.8	7.3
Liquid gas consumption	kg/h	3.1	4.3	5.6
Gas connection	inches	1"	1"	1"
Motors power	kW	0.62 (*+0.56/**+0.74)	0.87(*+0.56/**+0.74)	0.87(*+0.56/**+0.74)
Fuses	A	2 ÷ 4	2 ÷ 4	2 ÷ 4

Models with steam heating (*With length folder / **With length folder and pass through)

Power supply	V / ph / Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz
		380-415V 3~N 50Hz	380-415V 3~N 50Hz	380-415V 3~N 50Hz
		440-480V 3~ 60Hz	440-480V 3~ 60Hz	440-480V 3~ 60Hz
Steam working pressure	kPa (bar)	1000 (10)	1000 (10)	1000 (10)
Steam consumption	kg/h	50	67	85
Steam inlet	inches	3/4"	3/4"	3/4"
Condensed outlet	inches	1/2"	1/2"	1/2"
Motors power	kW	0.62 (*+0.56/**+0.74)	0.87(*+0.56/**+0.74)	0.87(*+0.56/**+0.74)
Fuses	A	2 ÷ 4	2 ÷ 4	2 ÷ 4